

# Messe München

## OVERVIEW OF HALLS



Messe München

Spaces/Rooms	Length in m	Width in m	Floor Space in m <sup>2</sup>
Halls A1–A6	161	71	approx. 11.000
Halls B1–B5	161	71	approx. 11.000
Hall B6 (High hall)	161	71	approx. 11.000
Halls C1–C6	139–143	71	approx. 10.000

The halls of Messe München set high standards in functionality, infrastructure and communication. Our 18 ultra-modern halls at ground level offer you spacious areas with ample natural light thanks to expansive glazing. All halls are fully vehicle-accessible due to the column-free construction

and ceiling heights of eleven to 16 meters. Delivery zones directly adjacent to the exhibition halls provide optimum conditions for loading and unloading exhibits. So exhibitors enjoy maximum flexibility during set-up and dismantling.



Entrances	Press Centers	Meeting/Briefing Rooms
Halls	Conference Rooms	Function Rooms

# Messe München

## OVERVIEW OF HALLS



Messe München

Technical Data	A1–A6 B1–B5	B6 (High hall)	C1–C6	B0
<b>Length</b>	161 m	161 m	139 m–143 m	65 m
<b>Width</b>	71 m	71 m	71 m	54 m
<b>Total exhibition area</b>	approx. 11,000 m <sup>2</sup>	approx. 11,000 m <sup>2</sup>	approx. 10,000 m <sup>2</sup>	approx. 3,500 m <sup>2</sup>
<b>Clear height of longitudinal wall</b> (hall perimeter between entrances)	approx. 5.70 m	approx. 7.80 m	approx. 5.70 m	approx. 4.00 m
<b>Clear height of hall girder supports</b> (hall sides)	approx. 10.75 m	approx. 15.25 m	approx. 10.75 m	–
<b>Clear height of tie</b> (hall center) <b>Lichte Höhe Trennwandschott</b> (hall C6)	approx. 11.50 m	approx. 16.00 m	approx. 11.50 m Hall C6: 8.95 m	4.20 m
<b>Hall floor</b>	Mastic asphalt	Mastic asphalt	Mastic asphalt	Parkett
<b>Permissible distributed load</b>	5 t/m <sup>2</sup> (50 kN/m <sup>2</sup> )	5 t/m <sup>2</sup> (50 kN/m <sup>2</sup> )	5 t/m <sup>2</sup> (50 kN/m <sup>2</sup> )	2 t/m <sup>2</sup> (20 kN/m <sup>2</sup> )
<b>Permissible point load</b> (support area 0.3 m x 0.3 m, spacing approx. 1.5 m) does not apply to utility duct cover	5 t (50 kN)	5 t (50 kN)	5 t (50 kN)	8 t (80 kN)
<b>Permissible floor compression</b> under wheel and individual loads	60 t/m <sup>2</sup> (600 kN/m <sup>2</sup> )	60 t/m <sup>2</sup> (600 kN/m <sup>2</sup> )	60 t/m <sup>2</sup> (600 kN/m <sup>2</sup> )	nach Prüfung
<b>Permissible vertical load</b> (bezogen auf angemietete Standfläche)	5 kg/m <sup>2</sup>	5 kg/m <sup>2</sup>	5 kg/m <sup>2</sup> Halls C5–C6: 20 kg/m <sup>2</sup>	5 kg/m <sup>2</sup>
<b>Entrance gates: (Size) and [Number]</b> Vehicular access permitted No vehicular access	(4.50 m x 4.50 m) [6] (2.50 m x 4.50 m) [4]	(4.50 m x 4.50 m) [8] (2.50 m x 4.50 m) [2]	(4.50 m x 4.50 m) [6] (2.50 m x 4.50 m) [4]	(12.50 m x 4.00 m) [1]
<b>Artificial illumination</b>	200 Lux/m <sup>2</sup>	200 Lux/m <sup>2</sup>	200 Lux/m <sup>2</sup>	400 Lux/m <sup>2</sup>
<b>Ventilation</b>	partly air-conditioned	partly air-conditioned	partly air-conditioned	partly air-conditioned
<b>Utility supply ducts transverse to hall length, axes spaced at</b>	5.00 m	5.00 m	4.50 m (*)	4.85 m
<b>Width of utility ducts</b>	0.35 m	0.35 m	0.35 m	0.35 m
<b>Width of utility duct cover</b>	0.43 m	0.43 m	0.43 m	0.43 m
<b>Utility connections:</b>				
– Water	DN 25/min. 3.5 bar	DN 25/min. 3.5 bar	DN 25/min. 3.5 bar	DN 25/min. 3.5 bar
– Wastewater	DN 100	DN 100	DN 100	DN 100
– Sprinklers	DN 50	DN 50	DN 50	DN 50
– Compressed air	DN 50/min. 10 bar	DN 50/min. 10 bar	DN 50/min. 10 bar	DN 50/min. 10 bar
– Gas (availability depending on area coverage)	DN 25/20 mbar	DN 25/20 mbar	DN 25/20 mbar	DN 25/20 mbar
<b>Electricity supply</b>	200 W/m <sup>2</sup>	200 W/m <sup>2</sup>	200 W/m <sup>2</sup>	200 W/m <sup>2</sup>
<b>Telecommunications</b>				
– User-neutral, wireline connections (phone, fax, analog, ISDN, DSL, LAN)	300	300	300	100
– Wireless phone connections (DECT)	approx. 100	approx. 100	approx. 100	approx. 50
<b>Wideband connections (TV)</b>	150	150	150	56
<b>Fiber-optic connections</b> (Single-mode and/or gradient)	150	150	150	56

(\*) Hall C1 also has two utility ducts along the longitudinal axis of the hall.